

UPS / NO-BREAK DE 1500 VA

Interactive Line Uninterruptible Power System

epcom[®]
POWER ⚡ LINE

EPU1500LCD

Features:

- LCD display.
- Micro-processor based in digital control.
- AVR Boost and buck for voltage stabilization.
- Frequency autosensing.
- Humanized alarm system.
- Autotest during startup.
- Fresh start.
- Auto-restart when power is restored.
- Output simulated sine wave.
- Smart battery management.
- Shortcircuit, battery overload / overdischarge, overload, surge protection.
- Automatic charging in power off mode.
- Power off with no charging optional.
- Optional communication port RS-232 / USB and protection for RJ-11 / RJ-45 (optional).



Model	EPU1500LCD	
Capacity	1500 VA/ 900 W	
Input		
Voltage	100 Vac / 110 Vac / 120 Vac \pm 10%	
Frequency	50 / 60Hz \pm 1% (auto-sensed)	
Output		
Voltage	100 Vac / 110 Vac / 120 Vac \pm 10%	
Frequency	50 / 60 Hz \pm 1% (auto-sensed)	
Waveform	Simulated sine wave	
Transfer time	Typical 2 ~ 7 ms	
Batteries		
Voltage CC	12 Vcc	
Configuration	2 \times 12 Vcc / 8.0 Ah	
Charging time	6 ~ 8 h	
Communication		
Connectors	6 connectors NEMA 5-15R (4 backup and 2 protection)	
Protections	Shortcircuit – Battery overload – Overdischarge – Surge - Overtensions RJ-45 Protection	
USB / RS232 / SNMP (optional)	Compatible Windows [®] 98/2000/2003/XP/Vista/2008/Windows [®] 7/8/10	
Others		
Humidity	20 ~ 90% RH @ 0 ~ 40 (non condensed)	
Noise level	\leq 45 dB (1 m)	
Packing information	Net/gross weight (kg)	10.7 / 11.2
	Dimensions (mm) Width x Height x Depth	140 \times 345 \times 170
	Packing dimensions (mm) Width x Height x Depth	198 \times 406 \times 245