

## HikCentral-P-VSS-Base/HW/300Ch(B)



- Live View and Playback
- Visual Tracking
- Recording and Storage
- Event Management
- Network Management



## Specification

Model		HikCentral-P-VSS-Base/HW/300Ch(B)
	Cameras	300
Devices and Resources	Alarm Inputs	300
	Alarm Outputs	300
	Areas	300
	Cameras per Area	64
	Alarm Inputs per Area	64
	Alarm Outputs per Area	64
Recording	Recording Schedule	3000
	Recording Schedule Template	200
Event and Alarm	Event and Alarm Rules	3000
	Storage of Events or Alarms without Pictures	100/s
	Events or Alarms Sent to Clients *The clients include Control Clients and Mobile Clients	120/s 100Clients/s
	Notification Schedule Templates	200
Picture	Picture Storage *Including event/alarm pictures, face pictures, and vehicle	20/s (Stored in SYS Server) 80/s (Stored in Recording Server)



	pictures.	
Reports	Regular	
	Report Rules	100
	Event or Alarm Rules in One Event/Alarm Report Rule	32
	Records in One Sent Report	10,000 or 10 MB
	Resources Selected in One Report *With this limitation, you can generate a neat and clear report via the Control Client and it costs less time.	20
Users and Roles	Concurrent Accesses via Web Clients and Control Clients	100
	Concurrent Accesses via Mobile Clients	100
	Users	3000
	Roles	3000
	CPU	Intel® Xeon® E-2324G
	Memory	16G DDR4 DIMM slots, Supports UDIMM, up to 2666 MT/s
	Hard Disk	1T 7.2K SATA×2
	Storage Array	Internal Controllers: SAS_H355
Hardware Specifications	Rated Power Consumption	Single 250W (Bronze) power supply
	Device Dimensions	Form Factor: Rack (1U) Chassis Width: 434.00mm (17.08 in) Chassis Depth: 595.63mm (23.45 in) (3.5"HHD) Note: These dimensions do not include: bezel, redundant PSU
	Package Dimension	750 mm × 614 mm × 259 mm (29.53" × 24.17" × 10.2")



	Network	Integrated Intel I219-LM Ethernet LAN 10/100/1000
	External	10 External USB:1 x USB Type-C 3.1 Gen 2;,5 x 3.1 Gen 1 Type-A (1 front, 4 rear),4 xUSB
	Interfaces	2.0,1xRJ-45,2x Displayport ,1x Serial,2 x PS/2
	Package	29cm × 9.26cm × 29.2cm
	Dimensions	(11.42" × 3.7" × 11.5")
Physical and Environment al Parameters	Net Weight	
	(without	12.2 kg
	package)	
	Gross Weight	
	(with	18.5 kg
	package)	

## Available Model

HikCentral-P-VSS-Base/HW/300Ch(B)



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







