


Audio Wire 18 AWG Shielded

Model Number:PROAUDIOS



Application

Voice,Speakers, Microphones Applications
Flexible Cable for Easy Installations
Ideal for any Audio System
Auto-control Systems

Standards

ISO 9001:2000
PVC Comply with the ROHS Directive 2002/95/EC

Flame resistance

IEC 60332-1
CM

Physical Characteristics

Conductor	18 AWG 7-STR Annealed Bare Copper Conductors Shielded
Insulation	FRNC Polyvinyl chloride, Ø 1.55±0.02 mm
Insulation Avg. Thickness	0.011" 0.28mm
Insulation Color	Black & Red
Twisting	2 Insulation twisted to the pair, 12.5 twists per meter
Rip Cord	Yes
Shielded	N/A
Sheath	CM Rated Polyvinyl chloride,Ø 4.1±0.2 mm
Sheath Avg. Thickness	0.0196" 0.50mm
Sheath Color	White RAL 9003

Electrical properties @ 20 °C

DC resistance	Max 23.00 ohm/1000M at 20 °C
Mutual capacitance	96.5 pf/M
Characteristic impedance 100 MHz	64 ± 5 Ω
Nominal velocity of propagation	approx. 55 %
Voltage Rating	300 V
Max. Current	3.75 A @ 20 °C
Temperature	-20 °C to 60 °C

Product Code Table

Product Description	Packing Length	Part Number
18 AWG STR AUDIO CABLE Shielded White	500ft Color box	PROAUDIOS