

Input Specifications

- Rated Voltage 100 to 240 VAC
- Variation Range 90 to 264 VAC
- Rate Frequency 50 to 60 Hz
- Variation Frequency 47 to 63 Hz
- Input Current 2 A rms (Max.) at lowest rated input voltage and max. output rated load
- Inrush Current 30 A (Max.) cold start at -48 VDC input, with rated load at 30°C
- AC Leakage Current 3.5 mA

Output Specifications

- Output Voltage +56 VDC
- Variation Range +56 to +56.6 VDC
- Output Current 0 to 1.1 A
- Peak Current 0.8 to 1.1 A
- Output Power 60 W
- Line Regulation ±3%
- Load Regulation ±5%
- Ripple and Noise 200 mVp-p
- Turn on Delay Time 2 s (Max.)
- Rise Time 40 ms (Max.)
- Hold Up Time 5 ms (Min.)
- Efficiency 80% (Min.)
- Overshoot 15% (Max.)

Protection Specifications

- Short Circuit Protection with auto recovery
- Over Current Protection with auto recovery
- Over Voltage Protection

Environmental Specifications

- Operating Temperature -10 °C to +40 °C
- Storage Temperature -20 °C to +85 °C
- Relative Humidity 5 to 90%

Safety Specifications

- Dielectric Strength 3000 VDC/5 mA/ s
- Safety Standards EN60950
- EMC FCC Part 15 Class B
EN55022 Class B

Mechanical Specifications

- Dimension 123 x 61 x 40 mm (Net)
465 x 300 x 190 (Gross)
- Weight 254 g (Net)

Reliability Specifications

- Operating Vibration IEC 721-3-3 3M3
- Transportation Vibration IEC 721-3-2 2M2
- Vibration Test 10 cycles per axis
- Drop Test 76 cm



Product Label



Product Ordering Information

- PoE Injector for A8n Series

Contact Us

- Email: sales@altaitechnologies.com

PE-PB-140303

Although Altai has attempted to provide accurate information in these materials, Altai assumes no legal liability for the accuracy and completeness of the information. All specifications are subject to change without notice.