



## Model: TX309-(xxx)

### Connector Suffix

### Radio Models

K01



KENWOOD TK3230/3000/3402/3312/3360/3170, NX240/340/220/320/420, TKD240/340

### Speaker Specification:

<b>Size:</b>	Ø 12.5 * 2.0 mm
<b>Sensitivity:</b>	92 ± 3 dB / 1 Watt 0.5 Meter
<b>Impedance:</b>	8 Ω ± 15% at 1000 Hz
<b>Frequency range:</b>	(F0) ~ 20 kHz
<b>Rated input power:</b>	F0 ~ 9 kHz
<b>Maximum input power:</b>	500 mW

### Microphone Specification:

<b>Size:</b>	Ø 6.0 * 2.7 mm
<b>Sensitivity:</b>	-30 ± 3 dB (0 dB = 1 V/Pa at 1 kHz)
<b>Impedance:</b>	2.2 kΩ 1 kHz (RL = 2.2 kΩ)
<b>Frequency:</b>	20 ~ 20 kHz (0 dB = 1 V/Pa, 1 kHz)
<b>Operation voltage range:</b>	1.0 - 10 V(DC)
<b>Operating voltage:</b>	1.0 V - 10 V(DC)

### Cable

<b>Diameter:</b>	Ø 5.5 mm
<b>Material:</b>	PU
<b>Operating temperature:</b>	-30 ~ 120°C