

**DS-7716NXI-K4/16P(E)(标配)**

- Automatic speed control fans are designed for running quietly and energy saving
- Adopt Hikvision AcuSense technology to minimize manual effort and security costs
- Efficient playback with AcuSearch technology
- Accurate perimeter protection effectively reduces false alarms
- Automatic cameras connection and configuration
- Up to 16-ch IP camera inputs, plug & play with 16 Power-over-Ethernet (PoE) interfaces
- H.265+/H.265/H.264+/H.264 video formats
- Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity
- Up to 160 Mbps incoming bandwidth

## ▪ Specification


Model		DS-7716NXI-K4/16P(E)(标配)
Intelligent Analytics	AI by NVR	Facial recognition, perimeter protection, motion detection 2.0, AcuSearch
	AI by Camera	Facial recognition, perimeter protection, motion detection 2.0, ANPR
Facial Recognition	Facial Detection and Analytics	Face picture comparison, human face capture, face picture search
	Facial Detection and Analytics Performance	Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch
	Face Picture Library	Up to 16 face picture libraries, with up to 50,000 face pictures in total (each picture ≤ 1 MB, total capacity ≤ 1 GB)
	Face Picture Comparison	8-ch
AcuSearch	By Camera	All channels *: The camera should enable AcuSearch function
Motion Detection 2.0	By NVR	All channels, up to 4 MP (when enhanced SVC mode is enabled, up to 8 MP) video analysis for human and vehicle recognition to reduce false alarm
	By Camera	All channels
Perimeter Protection	By NVR	Video analysis (HD network camera, H.264/H.265) for human and vehicle recognition to reduce false alarm. Up to 4 MP: 2-ch; 8 MP to 5 MP: 1-ch
	By Camera	All channels
Video and Audio	IP Video Input	16-ch
	IP Speaker Input	4-ch
	Incoming Bandwidth	160 Mbps
	Outgoing Bandwidth	160 Mbps
	HDMI Output	1-ch, 4K (3840×2160)/30Hz, 2K (2560×1440)/60Hz, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
	VGA Output	1-ch, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz
	Video Output Mode	HDMI/VGA independent output
	Audio Output	1-ch, RCA (Linear, 1 kΩ)
	Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 kΩ, using the audio input)
Decoding	Decoding Format	H.265, H.265+, H.264, H264+
	Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
	Synchronous Playback	16-ch

	Decoding Capability	AI on: 16-ch@1080p (30 fps) AI off: 20-ch@1080p (30 fps)	
	Stream Type	Video, Video and Audio	
	Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2	
Network	Remote Connection	128	
	API	ONVIF (profile S/G); SDK; ISAPI	
	Compatible Browser	IE 11, Chrome 91, Firefox 88, Safari 12, Edge 91, or above version	
	Network Protocol	TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS	
	Network Interface	1, RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces	
PoE	Interface	16, RJ-45 10/100 Mbps self-adaptive Ethernet interface	
	Power	≤ 200W	
	Standard	IEEE 802.3af/at	
Auxiliary Interface	SATA	4 SATA interfaces	
	Capacity	Up to 16 TB capacity for each HDD	
	Serial Interface	2 RS-485 (half-duplex), 1 RS-232	
	Alarm In/Out	16/4	
	eSATA	NA	
	USB Interface	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0	
General	GUI Language	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish, Norwegian, Finnish, Korean, Traditional Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Hebrew, Ukrainian, Indonesian	
	Fan	Supports	
	Power Supply	100 to 240 VAC, 50 to 60Hz	
	Consumption	≤ 50 W (without HDD)	
	Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)	
	Working Humidity	10 to 90 %	
	Dimension (W × D × H)	440 × 391 × 72 mm (17.32 × 15.39 × 2.82 inch)	
	Weight	≤ 5 kg (without HDD, 11 lb.)	
Certification	CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017	
	Obtained Certification	CE, CB, REACH, WEEE, UKCA, RCM, IC	

## ▪ Function


## ▪ Physical Interface

## DS-7716NXI-K4/16P(E)



No.	Description	No.	Description
1	Poe interfaces	8	RS-232 interface
2	USB 3.0 interface	9	ALARM IN
3	LAN network interface	10	ALARM OUT
4	AUDIO OUT	11	RS-484 interface
5	AUDIO IN	12	GND
6	HDMI interface	13	Power supply
7	VGA interface	14	Power switch

## DS-7716NXI-K4/16P(E)/IO16+9





No.	Description	No.	Description
1	PoE interfaces	9	RS-232 serial interface
2	USB 3.0 interface	10	ALARM IN
3	LAN network interface	11	ALARM OUT
4	eSATA interface	12	RS-485 interface
5	AUDIO OUT	13	GND
6	AUDIO IN	14	Power supply
7	HDMI interface	15	Power switch
8	VGA interface		

## ▪ Available Model

DS-7716NXI-K4/16P(E)

## ▪ Dimension



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

**HIKVISION®**