

DS-D4426RI-CQF



DS-D4426RI-CQF is the new generation indoor full-color rental LED display. LED display features in seamlessness, high brightness/contrast, wide viewing angle, and accurate color restoration, achieving good visual effect. It is widely used in places such as Stage performances, hotel weddings, festival celebrations, exhibitions, etc.

- Excellent in precision, heat dissipation, toughness, and solidity with the die-casting aluminum cabinet design.
- 500 mm × 500 mm cabinet with multiple dot pitches available and both indoor and outdoor scenarios applicable.
- Front maintenance available with the magnetic suction design, and quick front maintenance and installation achievable with the fixed installation of module at any position.
- 10-seconds replacement achievable with power supply, display controller, and adapter board integrated.
- Fast locking from the top, bottom, left, and right; 2-seconds locking for adjacent cabinets; convenient wiring with aviation plugs.
- Pendant mounting and standing available for installation.
- Free of fans and noise with excellent heat dissipation.
- High refresh rate (up to 3840 Hz) and high grey scale.



▪ Specification

Model		DS-D4426RI-CQF
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P2.6
	Pixel Pitch	2.604mm
	Modules Component	2 × 2
	Dimensions (W × H × D)	500 mm × 500mm × 90 mm
	Resolution	192 × 192
	Area	0.25 m ²
	Weight	7.9 Kg
	Pixel Density	112896 dots/m ²
	Lamp Board Housing	with housing
	Cabinet Material	Die-cast aluminum
	Cabinet Flatness	0.2 mm
	Protection Level	Front/Rear protection level IP45
Key Material	Lamp Encapsulation	SMD2121
	Driver IC	ICN2153
	Control System	Novastar
Display	White Balance Brightness	800 cd/m ²
	Color Temperature	3000 K to 10000 K adjustable
	Viewing Angle	Horizontal 120°, vertical 120°
	Contrast Ratio	≥ 6000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	3840 Hz

	Grey Level	14 bit
	Display Color	281 trillion
Power	Power Supply	220 VAC ± 15%
	Max. Consumption	≤ 450 W/m ²
	Average Consumption	≤ 135 W/m ²
Working Environment	Working Temperature	-20-50 °C
	Working Humidity	10%~80%RH
	Storage Humidity	10%~80%RH
	Storage Temperature	-20~60 °C
General	Gross Weight	85 Kg
	Package Dimension (W × H × D)	560 mm × 570 mm × 660 mm (6 IN 1)
	Lifespan	Lamp 100,000 hours



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 [10] 0351172
sale.africa@hikvision.com

Hikvision France
T +33[0]1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-[0]31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com