

DS-PS1-I-WB(B)
Wireless Internal Sounder



- 433 MHz two-way wireless communication
- Configurable arming/disarming prompt sound and LED indicator
- 3 years battery life span (triggered every two weeks and alerting 90 s for each triggering)
- AES-128 encryption
- Front and rear panel tamper-proof
- 3 kinds of alarm sounds: fire alarm, panic alarm, and intrusion alarm
- Buzzer Decibel: 90 to 110 dB
- Fully remote configurable through App
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission

▪ Specification

RF transmission	
RF Frequency	433 MHz
RF Modulation	2GFSK
RF Range	900m (open area)
Electrical characteristics	
Battery life span	Up to 3 years (standby time)
General	
Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
Operation humidity	10% to 90% (no condensing)
Shell material	PC+ABS
Dimension(WxHxD)	88× 88 × 32 mm (3.46" ×3.46" × 1.26")
Weight	169.5 g (6.0 oz)
Color	Blue/Red LED flash

▪ Available Model

DS-PS1-I-WB(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq