



PoE Injector

GS-PoE15W-MG/GS-PoE30W-MG/GS-PoE60W-MG

GS-PoE15W/30W/60W-MG are plug-and-play POE Injectors, which provide power for Grandstream's PoE powered devices, such as Wireless Access Points, IP phones, etc. They comply with IEEE 802.3af/at/bt standards. They have built-in power adapter with 1.2m AC cable, 1x 2.5Gbps RJ45 LAN IN and 1x 2.5Gbps RJ45 LAN OUT with PoE.

	GS-PoE15W-MG	GS-PoE30W-MG	GS-PoE60W-MG
Standards	IEEE 802.3 af	IEEE 802.3 af/at	IEEE 802.3 af/at/bt
Interface Ports	1xAC power Jack 1x2.5Gbps RJ45 LAN IN, 1x2.5Gbps RJ45 LAN OUT with PoE		
Input Voltage	100~240VAC, 50/60Hz		
Output Voltage	54VDC 1,2 +; 3,6 -		54VDC 1,2/4,5 +; 3,6/7,8 -
PoE Output Power	15.5W	30W	60W
LED	Power On: Blue PoE Load: Purple		
Environmental	Operation: 0°C to 45°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing		
Dimension (without Cable)	Unit: TBD Entire Package: TBD	Unit: TBD Entire Package: TBD	Unit: TBD Entire Package: TBD
Weight	Unit: TBD Entire Package: TBD	Unit: TBD Entire Package: TBD	Unit: TBD Entire Package: TBD
Package Content	GS-POE15W-MG, 1.2m AC Cable, Quick Installation Guide	GS-POE30W-MG, 1.2m AC Cable, Quick Installation Guide	GS-POE60W-MG, 1.2m AC Cable, Quick Installation Guide
Compliance	FCC, CE, RCM, IC		